**BACK** 

# **FRONT**

Description Engine

**HP Category** 

Model : S-15XM

: 14.91 - 18.64 kW (20-25 HP) : 4 Stroke, Direct injection Diesel

No. of cylinder **Bore & Stroke** : 120 x 136 mm

1537 cm<sup>3</sup> Displacement Rated engine speed 3-Stage Oil bath type

: Water cooled, with no loss tank Cooling system

Clutch : Single diaphragm type-280 mm diameter 279.40 (11)

No. of gears : 8 forward, 2 reverse speeds

Gear speed (km/h) 152.40 X 406.40 mm with (6\*16) front and

314.96 X 711.20 mm (12.40\*28) rear type 3.10 to 28.43 2.70 & 9.30 Reverse

1650 engine r/min for rated engine speed at 1000 r/min. 6 splines for 540 r/min (optional)

: Dry disc type brakes Hydraulics : Live hydraulics

i) Position control : To keep lower links on desired

ii) Automatic draft control : To keep uniform draft

: For maximum work capacity in

Lifting capacity : 1000 kg on lower link ends Linkage:

3-point linkage

iii) Mix control

: Suitable for 3-point linkage category-I, Category-II type implement pins

: Heavy duty single drop arm with mechanical steering for better

Weight & dimension Total length 3260 mm Total width 1690 mm Total Height 2395 mm Wheel base 1930 mm Minimum ground clearance 400 mm Tractor weight 1870 kg Wheel track Front 1330 mm Rear 1350 mm with 314.96 X 711.20 mm (12.40\*28 tyre size) 152.40 X 406.40 mm, 314.96 X Tyres 711.20 mm (Front 6.00 x 16, Rear 12.40 x 28) Electricals & instruments: Electricals : 12 volt, 88 A battery starter

motor & alternator headlight and parking lamps

: Engine r/min with direction

indicators & hour meter, fuel gauge, ammeter and water pressure gauge

♦ Single cylinder water cooled engine

♦ 279.40 (11) clutch for easy gear operation & long life

♦ 28.40 km/h for maximum speed-carrying work on road

♦ 1000 kg hydraulic lifting capacity

Big brakes for effective braking

Adjustable sliding P.U. seat for operator's comfort

Fuel tank capacity-45 litre


Easy reach to fuel tank system & transparent water separator for timely water drainage

Adjustable rod for more transport height

High capacity 88 A battery for easy start & long life

♦ Isolator valve for ancillary use

\*For product improvements specifications are subject to change without any prior notice.





### **SWARAJ DIVISION**

Phase IV, Industrial Area, S.A.S Nagar (Mohali), Punjab - 160055, Phone: 0172 2271620 to 27; 0172 2270820 to 23. Website: www.swarajtractors.com

**Authorised Dealer:** 



INSIDE 2 INSIDE 3





# **Single Cylinder Water Cooled Engine**

- **Powerful:** More back up/ maximum torque gives sufficient power on slopes
- Fuel efficient: Less consumption due to less SFC
- Water cooled: Engine temperature remains balanced due to water cooled engine, hence low maintenance of engine.
- **1650 rated r/min:** Full power & less engine wear during haulage & farming due to rated r/min.


### **Raised Surface**

• Tough driving conditions like sand eviction & to pull brick loaded trolley without breaking motion.




Swaraj Tractor is the first assurance of customer. Its attractive style increases their enthusiasm. To operate with pride, Swaraj Tractor is really a complete tractor loaded with unlimited features.

#### POWERFUL ENGINE



Fuel efficient water-cooled engine. Better pulling

#### TRANSPORT LOCK



Locks the implement at desired places

#### BIG DISC BRAKES



Effective braking on slopes with trailer

# TAP OFF CONNECTION



Connect outer hydraulic attachments with ease

#### MAXIMUM SPEED ON ROAD



More speed,more work, more

Top link is adjustable according to soil requirements


TOP LINK ARRANGEMENT

WITH DIFFERENT HOLES

#### **BETTER ERGONOMICS**



Fuel tank with 45-litre capacity



More comfort for driver