www.swarajtractors.com

Swaraj 841XM with Leveller




















Specifications

Engine	
Model	: MDI 2385S 3A
HP grade	: 29.82 kW (40 HP) range
Туре	: 4 stroke, direct injection, diesel engine
Number of Cylinders	: 4
Boar and stroke	: 88.90 × 110 mm
Displacement	: 2730 cm ³

Rated Engine Speed Air Cleaner 3-stage oil bath type Cooling System Water cooled with no loss tank

Clutch

Single diaphragm type 280 mm diameter, Dual clutch 280 mm diameter (optional) Number of Gears

8 forward, 2 reverse speed, gear speed (km/h) with 152.40 X 406.40 mm (6.00 x 16) front and 314.96 X 711.20 mm (12.40 x 28) rear type

Reverse

P.T.O. Live P.T.O. 540 r/min with similar to 1800 r/min engine Oil immersed brakes

Hydraulics A) Live Hydraulics

B) Sensilift hydraulics for better performance in pulverized and sandy land A) Position control : To hold lower links at any desired height

B) Automatic Draft Control: To maintain uniform depth

: For simultaneous use of position and draft controls for optimum field output C) Mix Control

Lifting capability 1200 kg at lower link ends

3-point suitable for Category-I & Category-II type implement pins

: Heavy duty single drop arm steering for high efficiency and comfortable drive

Full length Full width Full height Wheel base

Min. ground clearance 293 mm

1820 kg Weight of tractor

Wheel Track Front 1335 - 1565 mm Rear 1350 - 1890 mm {With 314.96 X 711.20 mm (12.40 x 28) tyre size}

Standard : Front 152.40 X 406.40 mm (6.00 x 16), Rear 314.96 X 711.20 mm (12.40 x 28)

{Optional Front 152.40 X 406.40 mm (6.00 x 16), Rear 345.44 X 711.20 mm (13.60 x 28)} Electricals and Instruments

12 volt 88 A battery, starter motor and alternator

r/min and hour meter, direction indicators, ammeter, fuel gauge, water temperature gauge and oil

eatures of New and advance hydraulics

Live Hydraulics

Electricals

Advanced and sensilift hydraulics for better performance in pulverized and sandy land

Controlled loading speed for better hydraulic operation in pulverized and sandy land

> Square lift rod provided to get more transport height

> Acquired slide adjustable stabilizer bar for implement swing control

Transport lock provided for heavy loads/machines > 1200 kg lifting capacity

Isolator valve like tipping trolley for external use

*For improvements in the products, specifications could be changed zout prior notice. The model shown here is only for representative purpose. Actual product may defer.

Warranty: 2 years or 2000 hours, whichever is earlier



SWARAJ DIVISION,

Phase IV, Industrial Area, S. A. S. Nagar, Mohali, Punjab-160 055. Phone: 0172 2271620 to 27; 0172 227820 to 23 Website: www.swarajtractors.com

Authorised dealer:















Sensilift hydraulics is specifically made by Swaraj to work easily in pulverized and sandy lands. Sensilift hydraulics is specifically made with better control valve which helps in maintaining uniform depth in sowing and pushes the sandy mud to make proper level. Sensilift hydraulics is available in 1200 kg capacity which helps in lifting the trolley with heavy load and is useful to work with heavy equipments like Disc Harrow and Seed Drill.

Special features of Sensilift hydraulics:

- + 3 point linkage compatibility: Pulls maximum mud with minimum resistance in levelling work
- + 1200 kg Life Capacity: Operates heavy equipments easily
- → Live Hydraulics: Hydraulics work even after releasing the clutch
- + Transport Height: Easily does field work on sandy slopes and crosses the ram.



Better hydraulic lever Easy operation



Hydraulic pump with more flow Hydraulic works quickly and in a better way



Better control valve Helps in maintaining uniform depth in sowing and pushes the sandy mud to make proper level.

Swaraj tractor, the first choice of the farmers. A powerful engine with 1900 rated r/min makes every job easy and increases the life of the tractor. Unparalleled features and attractive design make Swaraj Tractor, an invaluable asset for its farmer.



Strong efficient engine for longer life and more saving

8F+2R, Sliding and Constant mesh with gears Easy gear shifting and comfortable drive



Single drop arm



Compact design Light weight and compact design protects it from sandy mud from slipping



Oil immersed brakes for powerful braking



Smaller turning radius



Diaphragm clutch For longer life and more comfort



Mobile charging point Charge your mobile while working on the



345.44 X 711.2 mm (13.6 x 28) rear tyre For strong hold in tillage and other work

