

ENG_Q_2019_MAR_M & M LTD (SWARAJ)_SWARAJ_11140232_PM_11 (W)X8(H) IN_855 FE DT PLUS LEAFLET_4 PAGER_R1

BACK

STEERING : Steering Type Independent power steering HYDRAULICS AND IMPLEMENT LINKAGE

2 lever live hydraulic system having automatic position with draft control.

A) Position Control: To hold lower links at any desired height.

B) Automatic Draft Control: To maintain uniform depth

Mix Control: For simultaneous use of position and draft controls for optimum field output.

C) Hydraulic Lift Pump: Gear type hydraulic pump delivers 27 I/min at rated engine speed.

LINKAGE : 3-point linkage suitable for Category-I & Category-II type implement pins.

Water cooled with no loss tank, Oil LIFTING CAPACITY : 1700 kg at lower link ends

ELECTRICALS & ELECTRONICS

Electricals: 12 volt, 99 A, battery, starter motor and alternator

INSTRUMENTS : Digital Cluster

TYRES

Standard 190.50 X 406.40 mm Front Tyre (7.50 x 16)

: Standard 378.46 X 711.20 mm (14.90 x 28)

Optional- 429.26 X 711.20 mm

(16.90 x 28)

WEIGHTS & DIMENSIONS

O.A. Length : 3540 mm OA Width 1805 mm O.A. Height : 2256 mm Wheel Base 2245 mm Min. Ground Clearance Weight of Tractor : 2250 kg

Wheel Track : Front 1380 - 1440 mm

Rear 1420 - 1820 mm

FEATURES

- Ultramodern oil cooler- for longer engine life

· Higher capacity hydraulic (1700 kg) with improved sensitivity

· Oil Immersed Brakes

• Bigger front tyres - 190.50 X 406.40 (7.50 x 16) Bigger rear tyres – 378,46 X 711,20 (14,90 x 28) and

429.26 X 711.20 (16.90 x 28) (optional)

· Power steering

· Multi speed forward & reverse PTO (CR PTO)

 DCV – External hydraulic usage · Heavy duty casted front axle bracket

· Bigger & comfortable P.U. sliding driver seat

· Digital instrument cluster

Highly suitable tractor for compressor, reaper machine,

haulage, agricultural works

Specifications are subject to change without notice for product improvement. The model shown here is for representational purpose only. The actual product may vary. Accessories and implements shown here may not be part of standard product.

Warranty: 2 years or 2000 hours, whichever is earlier.

304.80 mm(12) IPTO, no. of Gears: 8 forward,

2 reverse speeds with high and low selector lever,

- RV-33 T

:110 x 116 mm

: 3308 cm³

: 2000 r/min.

the life of engine

: 2.63 & 30.91

: 3.31 & 12.94

cooler for engine oil,

: 37.28-41.01 kW (50-55 HP)

: 3 stage air cleaning cyclonic

pre-cleaner with oil bowl and

paper element which increases

: PTO Speed: 540 r/min, multi speed

: Brake Type: Oil immersed brakes

forward & reverse PTO

with extra parking brakes

: 4 - Stroke, Direct Injection, Diesel



ENGINE

Model

Engine.

HP category

No. of Cylinders

Bore and stroke

Rated Engine Speed

Displacement

Air Cleaner

Cooling System:

TRANMISSION

Clutch Type /Size:

PTO

BRAKES:

GEAR SPEEDS (km/h)

SWARAJ DIVISION

Phase IV, Industrial Area, S.A.S Nagar (Mohali), Punjab - 160055. Phone: 0172 2271620 to 27: 0172 2270820 to 23 Website: www.swarajtractors.com



ENG_Q_2019_MAR_M & M LTD (SWARAJ)_SWARAJ_11140232_PM_11 (W)X8(H) IN_855 FE DT PLUS LEAFLET_4 PAGER_R1