

ADVANTAGES

- Baler can be operated in lower-HP tractors. Trouble free binding easy adjustments.
- Easy to pick, store & transport. Lubrication system with self cleaning brush. Bale Counter.

SWARAJ ROUND BALER M BRAND FEATURES

- Automatically operated twine-binding system.
- Automatically operated centralised lubrication system
- Bale density can be adjusted
- The larger tires absorb shock loads in rough terrain and improve flotation on soft ground.
- Spring-loaded bale ramp allows the bale to roll away from the baler.
- No external power supply required to operate Hydraulic system



TECHNICAL SPECIFICATION

TYPE	PICK UP WIDTH	BALE DIMENSION	BALE WEIGHT	BINDING TYPE	BALE CAPACITY	TRACTOR POWER	PTO SPEED	HITCHING	DIMENSION	WEIGHT
Tractor PTO Operated Round Baler	1065 mm (with side cover)	610 x 930mm	20-35 kgs	Twine	24-30 Bale per hour	25-45 HP (Dual Clutch Must)	540 RPM	CAT-II 3-Point linkage	1550 x 1450 x 1250 L x W x H	600 kgs





Centralised self lubrication system with cleaning brush



Hydraulic bale eject system



Pick up unit

Dealer Stamp

